



TECHNICAL SPECIFICATIONS

Pro-Tech™ Rope

General Work Products registered trademark Pro-Tech™ is one of the strongest co-polymer ropes in the market today. The Teal color fiber with two International Orange tracers have become the industry standard for high performance marine rope. Manufactured from high tenacity polyolefin yarns, Pro-Tech-3S™ offers easy handling, high strength, excellent abrasion resistance and excellent UV characteristics.

FEATURES

- Super strength and easy handling
- Excellent UV and abrasion resistance
- High-performance marine rope
- No loss of strength when wet and floats
- Specific gravity 0.91
- Available in a variety of put-ups, 3-strand, 8 braid and 12-strand

APPLICATIONS

- Shipping
- General Marine
- Industrial
- Transmission
- General Purpose



Part #	Diameter	Length	Color	Minimum Breaking Strength (lbs.)
PROTECH5/1612	5/16"	1,200'	Teal w/ International Orange Tracer	3,100
PROTECH3/8	3/8"	600'	Teal w/ International Orange Tracer	3,800
PROTECH3/812	3/8"	1,200'	Teal w/ International Orange Tracer	3,800
PROTECH7/16	7/16"	600'	Teal w/ International Orange Tracer	4,700
PROTECH1/2	1/2"	600'	Teal w/ International Orange Tracer	6,600
PROTECH5/8	5/8"	600'	Teal w/ International Orange Tracer	11,000
PROTECH3/4	3/4"	600'	Teal w/ International Orange Tracer	13,900
PROTECH3/412	3/4"	1,200'	Teal w/ International Orange Tracer	13,900
PROTECH7/8	7/8"	600'	Teal w/ International Orange Tracer	20,100
PROTECH1	1"	600'	Teal w/ International Orange Tracer	23,100
PROTECH1-1/8	1-1/8"	600'	Teal w/ International Orange Tracer	23,100
PROTECH1-1/4	1-1/4"	600'	Teal w/ International Orange Tracer	23,100
PROTECH1-1/2	1-1/2"	600'	Teal w/ International Orange Tracer	46,100
PROTECH1-3/4	1-3/4"	600'	Teal w/ International Orange Tracer	66,500
PROTECH23	2"	300'	Teal w/ International Orange Tracer	83,500
PROTECH2	2"	600'	Teal w/ International Orange Tracer	83,500

Specifications are subject to change without notice. General Work Products makes no warranties to the use for a specific use or installation of products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage. General Work Products recommends installing the herein specified products in accordance with ANSI A-10-11-1989 and OSHA 1926.502 or all applicable local, state or federal requirements. Correct installation is the sole responsibility of the user/installer.