



## TECHNICAL SPECIFICATIONS



Combining Small Diameters with High Breaking Strengths, the Tightest Rope with the Highest Breaking Strengths.



Diameter		Circumference	Weight	Minimum Breaking Strength*
(MM)	(INCH)	(INCH)	LB/100'	
5	3/16	9/16	1.0	4,900
6	1/4	3/4	1.6	7,700
8	5/16	1	2.7	12,300
9	3/8	1 1/8	3.6	17,600
11	7/16	1 1/4	4.2	21,500
12	1/2	1 1/2	6.4	30,600
14	9/16	1 3/4	7.9	36,500
16	5/8	2	10.2	47,500
18	3/4	2 1/4	13.3	58,000
22	7/8	2 3/4	19.6	81,700
24	1	3	21.8	98,100
28	1 1/8	3 1/2	31.9	133,000
30	1 1/4	3 3/4	36.2	149,000
32	1 5/16	4	41.8	166,000
34	1 3/8	4 1/8	45.0	185,000
36	1 1/2	4 1/2	51.7	205,000
40	1 5/8	5	65.2	255,000
44	1 3/4	5 1/2	78.4	302,000
48	2	6	87.0	343,000
52	2 1/8	6 1/2	109.0	411,000
56	2 1/4	7	116.0	484,000
60	2 1/2	7 1/2	148.0	529,000
64	2 5/8	8	167.0	595,000
68	2 3/4	8 1/2	187.0	662,000
72	3	9	206.0	749,000
80	3 1/4	10	244.0	915,000
96	4	12	343.0	1,270,000

GENERAL	SECTORS
<ul style="list-style-type: none"> <li>• 12-Strand Braided Rope Made of HMPE</li> <li>• Commonly Known as HMPE (High Modulus PolyEthylene)</li> <li>• Superior Abrasion Resistance</li> <li>• Very High Strength with Low Weight to Diameter Ratio</li> <li>• Easy in Handling and Operation</li> <li>• Comparable to Steel Wire Characteristics</li> </ul>	<ul style="list-style-type: none"> <li>• Passenger and Container Ships</li> <li>• Bulk Carriers</li> <li>• LNG and LPG Carrier Barges</li> <li>• Tugs, Harbor Towing and Dredgers</li> <li>• Fishing Vessels and Nets</li> </ul>

TECHNICAL DATA	
Material:	Ultra – High Molecular Weight Polyethethylene
Construction:	12-Strand Braided
Treatment:	Marine Finish
Color of Rope:	Blue or Orange
Approx. Specific Density:	0.975 Floating
Melting Point:	145° C
Abrasion Resistance:	Excellent
U.V. Resistance:	Good
Temperature Resistance:	70°C Max Continuous
Chemical Resistance:	Excellent
Dry & Wet Conditions:	Wet Strength Equals Dry Strength

MADE IN BELGIUM BY  
**BEXCO**



\* SPLICED STRENGTH

Specifications are subject to change without notice. General Work Products makes no warranties to the use for a specific use or installation of products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage. General Work Products recommends installing the herein specified products in accordance with ANSI A-10-11-1989 and OSHA 1926.502 or all applicable local, state or federal requirements. Correct installation is the sole responsibility of the user/installer.