



TECHNICAL SPECIFICATIONS

Class 2 Type R Safety Vests

Our hi-viz safety vest come in bright florescent colors with a reflective silver tape to ensure proper visibility. Perfect choice for crossing guards, utility, emergency work, airport luggage handlers, highways, and surveyors.

TECHNICAL DATA	
Features	<ul style="list-style-type: none"> • Class 2 Type R • Meets ANSI/ISEA 107-2015 • Meets ASTM D6413 • Meets OSHA 1910.269 • Self-Extinguishing* • Maximum visibility • Lightweight, Comfortable fit
Available sizes	Small, Medium, Large, X-Large, 2X-Large, 3X-Large, and 4X-Large.
Available colors	Hi-Viz Lime Green and Fluorescent Orange
Pockets	1 Front Chest and 1 lower inside front
*Garment is made from 100% Polyester treated to be Self-Extinguishing as defined by ASTM D6413 (<2.0 s flameout / <6.0" Char Length). This garment should never be used where an arc flash or flash fire hazard is present. This garment is not flame resistant as defined by ANSI/ISEA 107-2015 Section 10.5.	



Part #	Color	Size	Case
SVLS	Hi-Viz Lime Green	Small	25/Case
SVLM	Hi-Viz Lime Green	Medium	25/Case
SVLL	Hi-Viz Lime Green	Large	25/Case
SVLXL	Hi-Viz Lime Green	XL	25/Case
SVLXXL	Hi-Viz Lime Green	2XL	25/Case
SVL3XL	Hi-Viz Lime Green	3XL	25/Case
SVL4XL	Hi-Viz Lime Green	4XL	25/Case

Part #	Color	Size	Case
SVOS	Hi-Viz Fluorescent Orange	Small	25/Case
SVOM	Hi-Viz Fluorescent Orange	Medium	25/Case
SVOL	Hi-Viz Fluorescent Orange	Large	25/Case
SVOXL	Hi-Viz Fluorescent Orange	XL	25/Case
SVOXXL	Hi-Viz Fluorescent Orange	2XL	25/Case
SVO3XL	Hi-Viz Fluorescent Orange	3XL	25/Case
SVO4XL	Hi-Viz Fluorescent Orange	4XL	25/Case

Specifications are subject to change without notice. General Work Products makes no warranties to the use for a specific use or installation of products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage. General Work Products recommends installing the herein specified products in accordance with ANSI A-10-11-1989 and OSHA 1926.502 or all applicable local, state or federal requirements. Correct installation is the sole responsibility of the user/installer.