PN: H212100574



Phone: (504) 733-1808 Fax: (504) 733-2996 PalmerSafetyUS.com

TECHNICALSPECIFICATIONS

Hammerhead[™] Series Harness 5pt., Padded Back, Legs and Belt, QCB Chest and Legs, Back/Side D-Rings, Black



5 point harness, QCB, padded back sewn in, padded QCB legs. Positioning belt black. 3 D-rings. Oil and Dust Resistant, fall indicators. Multiple sizes. Meets or exceeds ANSI Z359.11-2021. A10.32-2012.



USER CAPACITY: 130 - 420 lbs.

DESIGN:	 One Dorsal D-Ring for fall arrest Adjustable shoulder straps for easy adjustment & Snug fitting Adjustable leg straps for snug fitting Two lanyard keepers have been incorporated to store unused leg of the lanyard Equipped with belt and two side D-rings for work positioning 		
	Material: Polyester Width: 1.73 in. (44mm) Breaking Strength: 5000 lbs. (Min.)		
STITCHING Thread:	Material: High Tenacity Polyester		
METAL Component:	Material: Alloy Steel Quick Locks and Aluminum D-Rings	Part #	Size
CONFORMS TO:	Meets or exceeds ANSI Z359.11-2021	H212100574	Universal
WEIGHT:	5.88 lbs	H212100574.2XL H212100574.3XL	2X-Large 3X-Large