

PN: H212100574

TECHNICAL SPECIFICATIONS

Harness 5pt., Padded Back, Legs and Belt, QCB Chest and Legs, Back D-Ring, and Side D-Rings

5 point harness, QCB, padded back sewn in, padded QCB legs. Positioning belt black. 3 D-rings. Oil and Dust Resistant, fall indicators. Multiple sizes. Meets or Exceeds ANSI Z359.11-2014. A10.32-2012.



USER CAPACITY: 130 - 420 lbs.

- DESIGN:**
- One Dorsal D-Ring for fall arrest
 - Adjustable shoulder straps for easy adjustment & Snug fitting.
 - Adjustable leg straps for snug fitting.
 - Two lanyard keepers have been incorporated to store unused leg of the lanyard.
 - Equipped with work positioning belt.
 - Equipped with two side D-Rings for work positioning.

WEBBING: Material: Polyester | Width: 1.73 in. \pm 0.008 in. (44mm \pm 0.2mm)
Breaking Strength: 5000 lbs. (Min.)

STITCHING THREAD: Material: High Tenacity Polyester

METAL COMPONENT: Material: Alloy Steel Quick Locks and Aluminum D-Rings

CONFORMS TO: Meets or Exceeds ANSI Z359.11-2014

HARNESS WEIGHT: 5.88 lbs. \pm 0.02 lbs.

Part #	Size
H212100574	Universal
H212100574.2XL	2X-Large
H212100574.3XL	3X-Large