

PN: H225100005



• Fall Protection • Competent Training • Netting • PPE

Phone: (504) 733-1808
Fax: (504) 733-2996
PalmerSafetyUS.com

TECHNICAL SPECIFICATIONS

Stingray™ Series FR Harness 5pt., QCB Chest and H-Style Legs, SRL Back Plate, Black



Para-Aramid/Aramid webbing, Para-Aramid stitching thread, Aramid label cover, Steel hardware, QCB steel chest, H style QCB Steel buckle leg straps, Back D-ring, SRL Back Plate. Universal size. Meets or exceeds ANSI Z359.11-2021. A10.32-2012.



USER CAPACITY: 130 - 420 lbs.

- DESIGN:**
- Flame Resistant Para-Aramid/Aramid Webbing
 - Full body Harness, 5 Point Adjustment, Dorsal D-ring
 - SRL Back Plate for easy dual connector installation
 - Steel Quick Connect Chest and H-Style Quick Connect Leg Straps
 - Breakaway Lanyard Keepers

WEBBING: Webbing Outer Shell: Aramid
Webbing Inner Core: Para-Aramid
Minimum Breaking Strength: 7,500 lbs.

METAL COMPONENT: Material: Alloy Steel

CONFORMS TO: Meets or exceeds ANSI Z359.11-2021