

PN: H225101005



• Fall Protection • Competent Training • Netting • PPE

Phone: (504) 733-1808  
Fax: (504) 733-2996  
PalmerSafetyUS.com

## TECHNICAL SPECIFICATIONS

### Stingray™ Series FR Harness 5pt., QCB Chest and H-Style Legs, SRL Back Plate and Side D-Rings, Black



Para-Aramid/Aramid webbing, Para-Aramid stitching thread, Aramid label cover, Steel hardware, QCB steel chest, H style QCB Steel buckle leg straps, Back D-ring, Side D-rings, SRL Back Plate. Universal size. Meets or exceeds ANSI Z359.11-2021. A10.32-2012.



**USER CAPACITY:** 130 - 420 lbs.

- DESIGN:**
- Flame Resistant Para-Aramid/Aramid Webbing
  - Full body Harness, 5 Point Adjustment, Dorsal D-ring and Side D-Rings
  - SRL Back Plate for easy dual connector installation
  - Steel Quick Connect Chest and H-Style Quick Connect Leg Straps
  - Breakaway Lanyard Keepers

**WEBBING:** Webbing Outer Shell: Aramid  
Webbing Inner Core: Para-Aramid  
Minimum Breaking Strength: 7,500 lbs.

**METAL COMPONENT:** Material: Alloy Steel

**CONFORMS TO:** Meets or exceeds ANSI Z359.11-2021