

PN: L113224



• Fall Protection • Competent Training • Netting • PPE

Phone: (504) 733-1808  
Fax: (504) 733-2996  
PalmerSafetyUS.com

## TECHNICAL SPECIFICATIONS

### Lanyard 6 ft. Tie Back, Urethane Coated, Shock Absorber, Small Hook, Double Leg

Lanyard 6' Double Leg Urethane Lanyard, Urethane Coated Webbing, Blue Shock Pack, 3/4" Hooks, Large Tie-back Rings on Each Leg, Rated 420 lbs., Meets or Exceeds ANSI Z359.13-2013.



- DESIGN:**
- Spark resistant urethane coated webbing.
  - Designed for tie-back use purpose when cross over and hook back to the D-Ring on the lanyard leg.

---

**WEBBING:** Material: Polyester & Urethane | Width: 1.22 in.  $\pm$  0.008 in. (31mm  $\pm$  0.2mm)  
Thickness: 0.13 in.  $\pm$  0.003 in. (3.2mm  $\pm$  0.1mm) | Breaking Strength: 7000 lbs.

---

**SHOCK PACK WEBBING:** Material: Polyester & Urethane | Width: 1.77 in.  $\pm$  0.008 in. (45mm  $\pm$  0.2mm)  
Thickness: 0.09 in.  $\pm$  0.003 in. (2.3mm  $\pm$  0.1mm) | Breaking Strength: 6000 lbs.

---

**METAL COMPONENT:** Material: Steel | Finish: Silver or yellow golden galvanized

---

**CONFORMS TO:** Meets or Exceeds ANSI Z359.13-2013; Max Arresting Force: 1800 lbs.; Average Arresting Force: 900 lbs., Max Arresting Distance: 48 in.

---

**CAPACITY:** ANSI 310 lbs. & OSHA 420 lbs.