

TECHNICAL SPECIFICATIONS

Palmer Safety Confined Space Tripod, Winch & 60' SRL-R System

This premium dual-system solution equips workers with both active retrieval and passive fall arrest. It features a heavy-duty tripod, a dedicated personnel winch, and a 60' 3-Way Self-Retracting Lifeline with Rescue capabilities, providing maximum versatility and safety for confined space entry.

INCLUDED COMPONENTS:

- **Confined Space 7' Tripod (CS717):** Aluminum alloy tripod with telescopic legs and a three-pulley head.
- **60' Personnel Winch (CS817):** Rescue winch equipped with 60 ft. of stainless steel wire rope and a swivel snap hook.
- **BEAST™ Series 60' SRL-R (SRL1211412):** Features galvanized steel wire rope, a robust steel casing, and a built-in hoisting winch to toggle between fall arrest and retrieval modes.
- **Tripod Mounting Bracket (CS2617):** Heavy-duty alloy steel bracket to securely mount the SRL-R to the tripod leg.



WORKING LOAD: 310 lbs. (140kg) Personnel Capacity (SRL-R Minimum Breaking Strength: 3,000 lbs.)

TOTAL SYSTEM WEIGHT: 115.8 lbs. (Tripod: 46.3 lbs. | Winch: 25 lbs. | SRL-R: 39.7 lbs. | Bracket: 4.8 lbs.)

RELEVANT STANDARDS: Meets or Exceeds ANSI Z359.18-2017, ANSI Z359.14-2021 Class 1, and ANSI Z359.4-2013